

Sync4j

Sync4j Exchange Connector 1.3 Admin Guide

Table of Contents

1. Introduction.....	3
1.1. Comments and Feedbacks.....	3
2. Architecture.....	4
2.1. The Big Picture.....	4
2.2. Sync4j Server DS – Exchange Server Communication.....	4
2.3. Security.....	5
2.3.1. Sync4j Server Authentication.....	5
2.4. ExchangeSyncSource Type.....	6
2.4.1. WebDAV.....	6
3. Installation and Administration.....	8
3.1. Sync4j Exchange Connector Registration.....	8
3.2. Configuration.....	8
3.2.1. Configuration examples.....	9
Exchange Contacts SyncSource.....	9
Exchange Calendar SyncSource.....	9
4. Internal design.....	10
4.1. Overview.....	10
4.2. Items Identification.....	11
4.3. Detecting and Applying Item Changes.....	12
4.4. Local Cache Database.....	12
4.5. Error Handling.....	13
4.6. Sync4j Exchange Connector dialog examples.....	13
4.6.1. Adding a contact.....	13
4.6.2. Updating a Contact.....	13
4.6.3. Listing Contacts.....	14
4.6.4. Deleting a Contact.....	14
4.6.5. Response to a Successful Addition.....	14
4.6.6. Response to a Successful Update.....	15
4.6.7. Response to a Failed Addition (not Existing URN).....	15
4.6.8. Response to a Successfully Deletion.....	16
4.6.9. Response to a Failed Deletion (Unexisting Contact).....	16
4.6.10. Adding an Appointment.....	16
4.6.11. Updating an Appointment.....	17
4.6.12. Listing Appointements.....	17
4.6.13. Deleting an Appointement.....	17
4.6.14. Selecting Appointment Items Modified after a Given Date.....	17
5. Sync4j Licensing.....	19
6. Appendices.....	20
6.1. References.....	20
6.2. Contact Properties.....	20
6.3. Calendar properties.....	22
6.4. Task properties.....	23
6.5. Note properties.....	23

1. Introduction

This document is intended for developers and administrators who have to manage Sync4j Exchange Connector 1.3.x. It includes:

- Architectural Overview
- Configuration and Administration

1.1. Comments and Feedbacks

The Sync4j Project team wants to hear from you! Please submit your questions, comments, feedbacks or testimonials to sync4j-users@lists.sourceforge.net.

2. Architecture

This section describes the architecture of the Sync4j Exchange Connector.

2.1. The Big Picture

The system architecture of the Sync4j Exchange Connector is shown in Figure 1.




Figure 1 - Sync4j Exchange Connector high level architecture

PIM data are stored in the Microsoft Exchange store and are managed by the Microsoft Exchange Server. When the server receives a synchronization request from a client addressed to one of the ExchangeSyncSource, the Local cache is queried for latest updates and, if any item has been updated client side or server side, the ExchangeSyncSource talks to the Exchange server through the WebDAV protocol.

Sync4j Exchange Connector is administered with a dedicated plug-in for the Sync4j Server DS administration tool *Sync4j Admin* by which an administrator can create/modify/delete ExchangeSyncSources.

2.2. Sync4j Server DS – Exchange Server Communication

The remote access protocol recommended by Microsoft in a distributed environment is WebDAV.

The WebDAV protocol is an extension to HTTP that you can use to build Web applications that are writable. Using WebDAV protocol methods, you can create, copy, delete, move, or search for resources in the Exchange store as well as set and search for resource properties.

The RFC 2518 specification defines extensions to the Hypertext Transfer Protocol 1.1 (HTTP/1.1), which is defined in RFC 2616. The extensions include a new set of protocol methods and request

headers used to move, copy, delete, and create collections of resources. Additionally, clients can set and get properties about resources along with the resource content itself.

The extensions relating to getting and setting properties require a rich format for data transfer. RFC 2518 defines the XML 1.0 as the format for wire data transfer. Additionally, a namespace in XML is required to provide scope for property names.

For more information about WebDAV see [2] and [3].

2.3. Security

Being WebDAV an HTTP based protocol, security and authentication is based on HTTP security and authentication.

NOTE: a standard Microsoft Exchange installation includes the WebDAV interface, which is based on IIS as web server. By default, IIS is configured to use the proprietary authentication protocol NTLM, which is implemented only in Internet Explorer. Since the ExchangeSyncSource uses raw HTTP requests to the Exchange server, IIS must be configured to use basic authentication. This is done through the Exchange System Manager, changing the options available on the panel *Administrative Groups / First Administrative Group / Servers / [server] / Protocols / Http / Exchange Virtual Server / Exchange*.

Authentication is also the mechanism used by Exchange server to support multiuser. When a WebDAV request is served, it allows to operate only with data belonging to the requesting user.

2.3.1. Sync4j Server Authentication

In order to check the credential provided by a user, the connector uses a specific Officer called *ExchangeOfficer*.

Using this Officer the credentials are checked directly on Exchange Server so it's required only to create the devices using the Sync4j Admin (see [7] for details about the Officer bean and the Sync4j Admin usage).

The ExchangeOfficer is automatically installed when the module is installed and the server configuration is changed in order to use this officer. You have only to update the file *Sync4j/server/config/sync4j/server/security/ExchangeOfficer.xml* with your Exchange Server information.

This is an example of the ExchangeOfficer.xml file:

```
<?xml version="1.0" encoding="UTF-8"?>
<java version="1.4.0" class="java.beans.XMLDecoder">
  <object class="sync4j.exchange.security.ExchangeOfficer">

    <void property="exchangeHost">
      <string>192.168.0.10</string>
    </void>

    <void property="exchangePort">
      <!-- default is 80 -->
      <int>80</int>
    </void>

    <void property="exchangeFolder">
      <!-- default is SugarWap -->
      <string>Exchange/Contacts</string>
    </void>

    <void property="serverAuth">
      <string>none</string>
    </void>
  </object>
</java>
```

IMPORTANT NOTE: the private information as the users passwords aren't stored in any Sync4j Server DS tables. The credentials are sent by the device in Base64 and they are used only to authenticate the user.

2.4. ExchangeSyncSource Type

The ExchangeSyncSource type is the mean the Sync4j Server DS interacts with the Exchange store. To do so, the sync source implements the needed WebDAV requests and interprets the received responses.

Because of differences in item handling between different item types (contacts, events, tasks, notes), four versions of ExchangeSyncSource type are provided:

- `sync4j.exchange.engine.source.ExchangeContactSyncSource`
- `sync4j.exchange.engine.source.ExchangeCalendarSyncSource`
- `sync4j.exchange.engine.source.ExchangeTaskSyncSource`
- `sync4j.exchange.engine.source.ExchangeNoteSyncSource`

All those classes, like any sync source, implement the `sync4j.framework.engine.source.SyncSource` interface and extend `sync4j.exchange.engine.source.ExchangeSyncSource`.

2.4.1. WebDAV

The Exchange store is a container of items, where each single item can, in turn, contains other items (in the case of folder items) or properties (in the case of data items).

Properties items can be queried and modified by a remote client through the WebDAV protocol. This is based on an extension of the HTTP protocol as transport protocol and on an XML based RPC protocol by which it is possible to query and modify items and properties.

The Exchange store is based on the item types shown in Figure 2. In this figure, item types are represented as groups of properties identified by an XML namespace.

- Exchange Store Schema
 - Content Classes
 - urn:content-classes:appointment
 - urn:content-classes:calendarfolder
 - urn:content-classes:calendarmessage
 - urn:content-classes:contactfolder
 - urn:content-classes:contentclassdef
 - urn:content-classes:document
 - urn:content-classes:dsn
 - urn:content-classes:folder
 - urn:content-classes:freebusy
 - urn:content-classes:item
 - urn:content-classes:journalfolder
 - urn:content-classes:mailfolder
 - urn:content-classes:mdn
 - urn:content-classes:message
 - urn:content-classes:notesfolder
 - urn:content-classes:object
 - urn:content-classes:person
 - urn:content-classes:propertydef
 - urn:content-classes:propertyoverride
 - urn:content-classes:recallmessage
 - urn:content-classes:recallreport
 - urn:content-classes:taskfolder
 - urn:schemas-microsoft-com:xml-data#ElementType

Figure 2 - Exchange store schema

The full list of the properties for each item type (contact, appointment, task and note) is available in Appendix A.

3. Installation and Administration

The Sync4j Exchange Connector is administered and configured through the Sync4j Admin interface. In this section, it is presented how to set up the Sync4j Server DS database in order to have the connector configured and the panel used to create and configure new sync sources based on the registered sync source types.

3.1. Sync4j Exchange Connector Registration

The connector is distributed as a Sync4j module (see [6]); the archive name is sync4j-exchange-1.3.x.zip.

After installing the module as describe in the administration guide [7], opening the Sync4j Admin you should have the new Sync4jConnector displayed. Expanding the children nodes you should have the tree shown in Figure 3.




Figure 3 - Sync4j Exchange Connector registration

In order to complete the Exchange Connector installation you have to set Exchange server host name (or ip address) and port parameters in the file:

Sync4j/server/config/sync4j/server/security/ExchangeOfficer.xml

3.2. Configuration

A ExchangeSyncSource is configured with the properties listed in the table below.

<i>Property</i>	<i>Description</i>
Source URI	The sync source URI
Name	The sync source name

<i>Property</i>	<i>Description</i>
Exchange Server	The Exchange server hostname/ip address.
Exchange Port	The Exchange server port.
Exchange Folder	exchange Server Name / exchange item folder e.g. Exchange/Contacts
Type	The Data content mime type.

3.2.1. Configuration examples

Exchange Contacts SyncSource

<i>Property</i>	<i>Value</i>
Source URI	./contacts
Name	contacts
Exchange Server	exchange.sync4j.org
Exchange Port	80
Exchange folder	Exchange/Contacts
Type	vCard

Exchange Calendar SyncSource

<i>Property</i>	<i>Value</i>
Source URI	./calendars
Name	calendars
Exchange Server	exchange.sync4j.org
Exchange Port	80
Exchange folder	Exchange/Calendar
Type	iCal

4. Internal design

The following sections describe how Sync4j Exchange Connector manages internal data and the algorithm for data synchronization. This information is not meant for administrator but for developers wanting to extend the capabilities of Sync4j Exchange Connector.

4.1. Overview

Sync4j Exchange Connector is composed of the logical modules shown in the collaboration diagram of Figure 4.




Figure 4 - Sync4j Exchange Connector collaboration diagram

ExchangeContactSyncSource, ExchangeCalendarSyncSource, ExchangeTaskSyncSource, ExchangeNoteSyncSource	This are the components to be plugged into the synchronization engine. They are implementation of the sync4j.framework.engine.source.SyncSource interface. These classes make use of the corresponding manager classes of the above layer in order to access the data layer. Not displayed by the figure, sync source and manager objects deal with the item data by the mean of the model classes Event, Contact, Task, Note.
CalendarManager, ContactManager, TaskManager, NoteManager	This classes create an interface layer on top of the data access layer and include the logic to retrieve the data associated to the items and to combine them in the model classes.
CalendarDAO, ContactDAO, TaskDAO, NoteDAO	This layer abstracts the access to the datasource (database for items status and Exchange store). The WebDAV XML messages returned by the Exchange server are parsed by WebDavXmlParser.
WebDavXmlParser	Is the class that interprets the WebDAV messages obtained by the server.
WebDavHttpTransport	This is the class that implements the connection logic to the Exchange server.

4.2. Items Identification

Any item in the Exchange store is addressed by a resource address and identified by a user-id. The resource address identifies an item by its name and position. For example /contact/home/John Brown.eml addresses a contact stored in a resource called John Brown.eml under the home subfolder.

The resource address is used mainly for update and delete operations, since they require to specify which resource is involved.

However, the resource url cannot be considered a long-term identification key because an item can be moved under different folders. For the purpose of uniquely identify an object in the Exchange store, the property repl-uid is used as it is associated to any item in the store.

The issue of creating new items in the Exchange store is resolved constructing a resource url as follows:

```
/<user>/<source uri>/<now timestamp>.eml
```

The item repl-uid assigned by Exchange is returned in the WebDAV response header as in the following example:

```
HTTP/1.1 207 Multi-Status
Server: Microsoft-IIS/5.0
Date: Tue, 20 Jan 2004 15:37:02 GMT
MS-Exchange-Permanent-URL: http://192.168.0.10/Exchange/fabio/-
FlatUrlSpace-/5eb
c95ae2cdf504c98296172915e02d2-5d/5ebc95ae2cdf504c98296172915e02d2-3e26
Repl-UID: <rid:5ebc95ae2cdf504c98296172915e02d2000000003e26>
Content-Type: text/xml
Content-Length: 436
ResourceTag:
<rt:5ebc95ae2cdf504c98296172915e02d2000000003e265ebc95ae2cdf504c982
96172915e02d2000000004dbb>
```

4.3. Detecting and Applying Item Changes

Two important properties stored along with an item in the Exchange store are `<a:creationdate>` and `<a:getlastmodified>` whose return respectively the item creation date and the item last modification timestamp. These properties are important when a fast sync is performed, since the sync source should query for changes happened since the last synchronization. However, when an item is physically deleted from the Exchange store, it disappears from the system and then there is no way to retrieve it or retrieve when it was deleted.

Therefore, a local items cache is needed in order keep track of the existing items at the time of the last synchronization. We call this database the *Local cache*.

The algorithm for changes detection is the following:

1. read all items repl-uid, resourceName, creationDate, lastModified from the Exchange store and put them in `exchangelItems`
2. read all items repl-id, lastModified, from the local cache and put them in `localItems`
3. foreach item `i` in `exchangelItems`
 1. if `i` is in `localItems`
 1. if `i.lastModified != localItems (i) lastModified`
 1. `i` is updated
 2. end if
 2. else
 1. `i` is new
 3. end if
4. foreach item `i` in `localItems`
 1. if `i` is not in `exchangelItems`
 1. `i` is deleted
 2. endif
5. endforeach

This procedure is executed in the `ExchangeSyncSource's beginSync()` method if the sync mode is one of the fast sync modes. The retrieved new, updated and deleted items are temporarily stored until the corresponding `getNew/Updated/DeletedSyncItem()` methods are called. When either `getNewSyncItems()` or `getUpdatedSyncItems()` are called by the sync engine, the corresponding items content is fetched by the Exchange store with proper WebDAV calls. All items must be returned in a single call.

Note that in the comparison steps, uids are compared and not resource urls.

If the sync mode is one of the slow sync modes, no step in the algorithm is done. When `getAllSyncItem()` is called by the sync engine, the items properties are fetched directly from the Exchange store, possibly in one single WebDAV call.

If the client sends items to add to the Exchange store, the new resource is created and the returned uid is added to the local cache.

In the case of client updates or deletes, the uid is used to look up the resource address in the `exchangelItems` list so that the obtained address can be used in the WebDAV call.

In the sync source's `endSync()` method read from Exchange Server the existing items, and are stored in the local cache (after cleaning it).

4.4. Local Cache Database

The local cache database is composed of the following tables:

SS_EXCH_ITEM_STATUS			
id	varchar(200)	primary key	Item unique identifier (repl-uid) in the syncsource specified by uri.
uri	varchar(128)	primary key	SyncSource uri.
principal	varchar(10)	index	Item owner.
last_modified	timestamp		item last modified on Exchange Server

Note that items ids are stored with their owner, who is the principal associated to the user who is performing the sync.

4.5. Error Handling

Any error should happen in the sync source results in a SyncSourceException being thrown. The error condition is logged before throwing the exception and optionally the cause can be set to the originating exception.

4.6. Sync4j Exchange Connector dialog examples

The following sections show some examples on how Sync4j Exchange Connector interacts with Exchange server through WebDAV.

4.6.1. Adding a contact:

```
PROPPATCH /Exchange/fabio/contacts/luigiafassina.eml HTTP/1.1
Host: 192.168.0.10
Content-Type: text/xml
Content-Length: 741
Authorization: Basic ZmFiaW86ZmFiaW8x

<?xml version="1.0" encoding="utf-8" ?>
<D:propertyupdate                                     xmlns:D="DAV:"
xmlns:EX="http://schemas.microsoft.com/exchange/"
xmlns:HM="urn:schemas:contacts:">
  <D:set>
    <D:prop>
      <D:contentclass>urn:content-classes:person</D:contentclass>
      <EX:outlookmessageclass>IPM.Contact</EX:outlookmessageclass>
      <HM:cn>Luigia Fassina</HM:cn>
      <HM:nickname>Lu</HM:nickname>
      <HM:email1>luigia.fassina@sync4j.org</HM:email1>
      <HM:title>Luigia Fassina</HM:title>
      <HM:fileas>luigiafassina</HM:fileas>
      <HM:givenName>Luigia</HM:givenName>
    </D:prop>
  </D:set>
</D:propertyupdate>
```

luigiafassina.eml on the first line is the key that uniquely identifies the item.

4.6.2. Updating a Contact

```
PROPPATCH /Exchange/fabio/contacts/luigiafassina.eml HTTP/1.1
Host: 192.168.0.10
Content-Type: text/xml
Content-Length: 741
Authorization: Basic ZmFiaW86ZmFiaW8x

<?xml version="1.0" encoding="utf-8" ?>
```

```

<D:propertyupdate                                     xmlns:D="DAV:"
xmlns:EX="http://schemas.microsoft.com/exchange/"
xmlns:HM="urn:schemas:contacts:">
  <D:set>
    <D:prop>
      <D:contentclass>urn:content-classes:person</D:contentclass>
      <EX:outlookmessageclass>IPM.Contact</EX:outlookmessageclass>
      <HM:cn>Luigia Fassina</HM:cn>
      <HM:nickname>Lu</HM:nickname>
      <HM:email1>lu@sync4j.org</HM:email1>
      <HM:title>Luigia Fassina</HM:title>
      <HM:fileas>luigiafassina</HM:fileas>
      <HM:givenName>Luigia</HM:givenName>
    </D:prop>
  </D:set>
</D:propertyupdate>

```

4.6.3. Listing Contacts

```

PROPFIND /Exchange/fabio/contacts HTTP/1.1
Host: 192.168.0.10
Depth: 1,noroot
Range: rows=0-9
Content-Type: text/xml
Content-Length: 741
Authorization: Basic ZmFiaW86ZmFiaW8x

```

```

<?xml version="1.0" encoding="utf-8" ?>
<D:propfind                                     xmlns:D="DAV:"
xmlns:EX="http://schemas.microsoft.com/exchange/"
xmlns:HM="urn:schemas:contacts:">
  <D:allprop/>
</D:propfind>

```

This example returns all fabio's contacts.

4.6.4. Deleting a Contact

```

DELETE /Exchange/fabio/contacts/luigiafassina.eml HTTP/1.1
Host: 192.168.0.10
Content-Length: 50
Authorization: Basic ZmFiaW86ZmFiaW8x

```

4.6.5. Response to a Successful Addition

```

HTTP/1.1 207 Multi-Status
Server: Microsoft-IIS/5.0
Date: Tue, 20 Jan 2004 15:31:28 GMT
MS-Exchange-Permanent-URL: http://192.168.0.10/Exchange/fabio/-
FlatUrlSpace-/5eb
c95ae2cdf504c98296172915e02d2-5d/5ebc95ae2cdf504c98296172915e02d2-3e26
Repl-UID: <rid:5ebc95ae2cdf504c98296172915e02d2000000003e26>
Content-Type: text/xml
Content-Length: 477
ResourceTag:
<rt:5ebc95ae2cdf504c98296172915e02d2000000003e265ebc95ae2cdf504c982
96172915e02d2000000004db6>
MS-WebStorage: 6.0.6249

```

```

<?xml                                     version="1.0"?><a:multistatus
xmlns:b="http://schemas.microsoft.com/exchange/"
xmlns:c="urn:schemas:contacts:" xmlns:a="DAV:">
<a:response>
<a:href>http://192.168.0.10/Exchange/fabio/Contacts/Johnniepippol1.eml</a:hr
ef>
<a:status>HTTP/1.1 201 Created</a:status><a:propstat><a:status>HTTP/1.1 200
OK</a:status>
<a:prop>
  <a:contentclass/><b:outlookmessageclass/><c:cn/><c:nickname/><c:email1/><c
:title/><c:fileas/><c:givenName/></a:prop></a:propstat></a:response></a:mul
tistatus>

```

The operation status is specified by the line:

```
<a:status>HTTP/1.1 201 Created</a:status>
```

4.6.6. Response to a Successful Update

```

HTTP/1.1 207 Multi-Status
Server: Microsoft-IIS/5.0
Date: Tue, 20 Jan 2004 15:37:02 GMT
MS-Exchange-Permanent-URL:           http://192.168.0.10/Exchange/fabio/-
FlatUrlSpace-/5eb
c95ae2cdf504c98296172915e02d2-5d/5ebc95ae2cdf504c98296172915e02d2-3e26
Repl-UID: <rid:5ebc95ae2cdf504c98296172915e02d2000000003e26>
Content-Type: text/xml
Content-Length: 436
ResourceTag:
<rt:5ebc95ae2cdf504c98296172915e02d2000000003e265ebc95ae2cdf504c982
96172915e02d20000000004dbb>
MS-WebStorage: 6.0.6249

```

```

<?xml                                     version="1.0"?><a:multistatus
xmlns:b="http://schemas.microsoft.com/exchan
ge/"                                     xmlns:c="urn:schemas:contacts:"
xmlns:a="DAV:"><a:response><a:href>http://1
92.168.0.10/Exchange/fabio/Contacts/Johnniepippol1.eml</a:href><a:propstat><
a:sta
tus>HTTP/1.1                                     200
OK</a:status><a:prop><a:contentclass/><b:outlookmessageclass/><
c:cn/><c:nickname/><c:email1/><c:title/><c:fileas/><c:givenName/></a:prop><
/a:pr
opstat></a:response></a:multistatus>

```

4.6.7. Response to a Failed Addition (not Existing URN)

```

HTTP/1.1 409 Conflict
Server: Microsoft-IIS/5.0
Date: Tue, 20 Jan 2004 15:41:51 GMT
Connection: close
Content-Type: text/html
Content-Length: 140
MS-WebStorage: 6.0.6249

```

```
<body><h2>HTTP/1.1 409 Conflict</h2></body></HTML>; charset=utf-8">
```

4.6.8. Response to a Successfully Deletion

```
HTTP/1.1 200 OK
Server: Microsoft-IIS/5.0
Date: Tue, 20 Jan 2004 15:45:43 GMT
Content-Length: 0
ResourceTag: <rtd:5ebc95ae2cdf504c98296172915e02d2000000003e26>
MS-WebStorage: 6.0.6249
```

4.6.9. Response to a Failed Deletion (Unexisting Contact)

```
HTTP/1.1 404 Resource Not Found
```

```
Server: Microsoft-IIS/5.0
Date: Tue, 20 Jan 2004 15:43:54 GMT
Connection: close
Content-Type: text/html
Content-Length: 4040
MS-WebStorage: 6.0.6249
```

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2 Final//EN">
<html dir=ltr>
```

```
<head>
<style>
a:link          {font:8pt/11pt verdana; color:FF0000}
a:visited       {font:8pt/11pt verdana; color:#4e4e4e}
</style>
```

```
<META NAME="ROBOTS" CONTENT="NOINDEX">
```

```
<title>The page cannot be found</title>
```

```
L'errore indicato è:
HTTP/1.1 404 Resource Not Found
```

4.6.10. Adding an Appointment

```
PROPPATCH /Exchange/fabio/calendar/calendarprova.eml HTTP/1.1
Host: 192.168.0.10
Content-Type: text/xml
Content-Length: 741
Authorization: Basic ZmFiaW86ZmFiaW8x
```

```
<?xml version="1.0" encoding="utf-8" ?>
<D:propertyupdate                                xmlns:D="DAV:"
xmlns:EX="http://schemas.microsoft.com/exchange/"
xmlns:HM="urn:schemas:calendar:" xmlns:e="urn:schemas:httpmail:">
  <D:set>
    <D:prop>
      <D:contentclass>urn:content-classes:appointment</D:contentclass>
      <EX:outlookmessageclass>IPM.Appointment</EX:outlookmessageclass>
      <e:subject>oggi telefonare al signor verri</e:subject>
      <HM:location>meetappt Location</HM:location>
      <HM:dtstart>2004-01-10T22:00:00.000Z</HM:dtstart>
      <HM:dtend>2004-01-10T22:30:00.000Z</HM:dtend>
    </D:prop>
  </D:set>
</D:propertyupdate>
```

4.6.11. Updating an Appointment

```
PROPPATCH /Exchange/fabio/calendar/calendarprova.eml HTTP/1.1
Host: 192.168.0.10
Content-Type: text/xml
Content-Length: 741
Authorization: Basic ZmFiaW86ZmFiaW8x
```

```
<?xml version="1.0" encoding="utf-8" ?>
<D:propertyupdate                                     xmlns:D="DAV:"
xmlns:EX="http://schemas.microsoft.com/exchange/"
xmlns:HM="urn:schemas:calendar:" xmlns:e="urn:schemas:httpmail:">
  <D:set>
    <D:prop>
      <D:contentclass>urn:content-classes:appointment</D:contentclass>
      <EX:outlookmessageclass>IPM.Appointment</EX:outlookmessageclass>
      <e:subject>oggi telefonare al signor rossi</e:subject>
      <HM:location>meetappt Location</HM:location>
      <HM:dtstart>2004-01-10T22:00:00.000Z</HM:dtstart>
      <HM:dtend>2004-01-10T22:30:00.000Z</HM:dtend>
    </D:prop>
  </D:set>
</D:propertyupdate>
```

4.6.12. Listing Appointments

```
PROPFIND /Exchange/fabio/calendar HTTP/1.1
Host: 192.168.0.10
Depth: 1,noroot
Range: rows=0-9
Content-Type: text/xml
Content-Length: 741
Authorization: Basic ZmFiaW86ZmFiaW8x
```

```
<?xml version="1.0" encoding="utf-8" ?>
<D:propfind                                     xmlns:D="DAV:"
xmlns:EX="http://schemas.microsoft.com/exchange/"
xmlns:HM="urn:schemas:calendars:">
  <D:allprop/>
</D:propfind>
```

4.6.13. Deleting an Appointment

```
DELETE /Exchange/fabio/calendar/calendarprova.eml HTTP/1.1
Host: 192.168.0.10
Content-Length: 50
Authorization: Basic ZmFiaW86ZmFiaW8x
```

4.6.14. Selecting Appointment Items Modified after a Given Date

WebDAV defines an SQL-like language through which execute generic queries on the Exchange store.

```
SEARCH /Exchange/fabio/calendar HTTP/1.1
Host: 192.168.0.10
Depth: 1,noroot
Range: rows=0-7
Content-Type: text/xml
Content-Length: 741
Authorization: Basic ZmFiaW86ZmFiaW8x
```

```
<?xml version="1.0" encoding="utf-8" ?>
<D:searchrequest xmlns:D = "DAV:" >
  <D:sql>
    Select  "urn:schemas:calendar:location" AS location,
            "urn:schemas:httpmail:subject" AS subject FROM
"/Exchange/fabio/calendar" WHERE "D:getlastmodified" > '1999/09/27
00:00:00'
  </D:sql>
</D:searchrequest>
```

5. Sync4j Licensing

Sync4j has two licensing options, following what is known as "dual licensing" model. After the adoption by [MySQL](#), this model is becoming very successful as a way to support open source development.

The guiding business principle of dual licensing is one of fair exchange, or Quid pro Quo ("something for something"). From a licensing perspective, there are two different products depending on usage and distribution, though technically they have the same source code.

- For those developing open source applications, the Open Source License allows you to offer your software under an open source / free software license (GPL) to all who wish to use, modify, and distribute it freely. The Open Source License allows you to use the software at no charge under the condition that if you use Sync4j in an application you redistribute, the complete source code for your application must be available and freely redistributable under reasonable conditions. Sync4j bases its interpretation of the GPL on the Free Software Foundation's Frequently Asked Questions.
- The Commercial License, which allows you to provide commercial software licenses to your customers or distribute Sync4j-based applications within your organization. This is for organizations that do not want to release the source code for their applications as open source / free software; in other words they do not want to comply with the GNU General Public License (GPL). If you want more information on pricing, please contact license@sync4j.org.

The idea is to get the best out open source (high quality software, a community of people working together, no vendor lock-in), while providing a source of income to pay for the development of the software (yep, Sync4j developers need to eat...).

In their simplest form, the following are general licensing guidelines:

- If your software is licensed under either the GPL-compatible Free Software License as defined by the Free Software Foundation or approved by OSI, then use our GPL licensed version.
- If you distribute a proprietary application in any way, and you are not licensing and distributing your source code under GPL, you need to purchase a commercial license of Sync4j

Commercially licensed customers get commercially supported product with assurances from Funambol. Commercially licensed users are also free from the requirement of making their own application open source.

For OEM's, ISVs, corporate, and government users, a commercial license is the proper solution because it provides you with assurance from the vendor and releases you from the strict requirements of the GPL license.

Nevertheless, you can test Sync4j under the GPL license and inspect the source code before you purchase a commercial non-GPL license.

6. Appendices

6.1. References

- [1] *SyncConnector Exchange Requirements Document*, October 2003
- [2] <http://www.webdav.org>
- [3] http://msdn.microsoft.com/library/default.asp?url=/library/en-us/wss/wss/wss_references_webdav.asp
- [4] Quartz Enterprise Job Scheduler, <http://www.quartzscheduler.org>
- [5] JBoss Administration and Development, Second Edition
- [6] Sync4j Modules Development Guide, Sync4j, February 2004
- [7] Sync4j SyncServer Administration Guide, November 2004
- [8] <http://www.devnewsgroups.net/link.aspx?url=http://www.cdolive.com/cdo10.htm>

6.2. Contact Properties

The following properties are associated to an Exchange contact item and supported by the connector:

<i>Property</i>
Anniversary
AssistantName
AssistantTelephoneNumber
Birthday
Body
Business2TelephoneNumber
BusinessAddressCity
BusinessAddressCountry
BusinessAddressPostalCode
BusinessAddressPostOfficeBox
BusinessAddressState
BusinessAddressStreet
BusinessFaxNumber
BusinessTelephoneNumber
BusinessWebPage

<i>Property</i>
CallbackTelephoneNumber
CarTelephoneNumber
Categories
Children
CompanyMainTelephoneNumber
CompanyName
Companies
ComputerNetworkName
Department
Email1Address
Email1AddressType
Email2Address
Email2AddressType
Email3Address
Email3AddressType
FileAs
FirstName
Hobby
Home2TelephoneNumber
HomeAddressCity
HomeAddressCountry
HomeAddressPostalCode
HomeAddressPostOfficeBox
HomeAddressState
HomeAddressStreet
HomeFaxNumber
HomeTelephoneNumber
HomeWebPage
Importance
Initials
JobTitle
Language
LastName
ManagerName
MiddleName
Mileage
MobileTelephoneNumber

<i>Property</i>
NickName
OfficeLocation
OtherAddressCity
OtherAddressCountry
OtherAddressPostalCode
OtherAddressState
OtherAddressStreet
OtherFaxNumber
OtherTelephoneNumber
PagerNumber
Profession
Sensitivity
Spouse
Subject
Suffix
TelexNumber
Title
WebPage

6.3. Calendar properties

The following properties are associated to an Exchange calendar item and supported by the connector:

<i>Property</i>
AllDayEvent
Body
BusyStatus
Categories
End
Importance
Location
MeetingStatus
Mileage
ReminderMinutesBeforeStart
ReminderSet
ReplyTime
Sensitivity

<i>Property</i>
Start
Subject

6.4. Task properties

The following properties are associated to an Exchange task item and supported by the connector:

<i>Property</i>
Body
Categories
Complete
DueDate
Importance
Mileage
PercentComplete
ReminderSet
ReminderTime
Sensitivity
StartDate
Status
Subject

6.5. Note properties

The following properties are associated to an Exchange note item and supported by the connector:

<i>Property</i>
subject
date
body