



Sync4j SyncConnector Exchange 1.0 Admin Guide

Table of Contents

1. Introduction.....	3
1.1. Comments and Feedbacks.....	3
2. Architecture.....	4
2.1. The Big Picture.....	4
2.2. SyncServer – Exchange Server Communication.....	4
2.3. Security.....	5
2.3.1. SyncServer Authentication.....	5
2.4. ExchangeSyncSource.....	5
2.4.1. WebDAV.....	5
3. Installation and Administration.....	7
3.1. SyncConnector Exchange Registration.....	7
3.2. Configuration.....	8
4. Internal design.....	9
4.1. Overview.....	9
4.2. Items Identification.....	10
4.3. Detecting and Applying Item Changes.....	11
4.4. Local Cache Database.....	11
4.5. Error Handling.....	12
4.6. SyncConnector – Exchange dialog examples.....	12
4.6.1. Adding a contact:.....	12
4.6.2. Updating a Contact.....	12
4.6.3. Listing Contacts.....	13
4.6.4. Deleting a Contact.....	13
4.6.5. Response to a Successful Addition.....	13
4.6.6. Response to a Successful Update.....	14
4.6.7. Response to a Failed Addition (not Existing URN).....	14
4.6.8. Response to a Successfully Deletion.....	14
4.6.9. Response to a Failed Deletion (Unexisting Contact).....	15
4.6.10. Adding an Appointment.....	15
4.6.11. Updating an Appointment.....	15
4.6.12. Listing Appointments.....	16
4.6.13. Deleting an Appointment.....	16
4.6.14. Selecting Appointment Items Modified after a Given Date.....	16
5. Sync4j Licensing.....	18
5.1. Copyrights and Licenses Used by Funambol.....	18
5.2. Using the Sync4j Software Under a Commercial License.....	18
5.3. Using the Sync4j Software for Free Under GPL.....	19
6. Appendices.....	20
6.1. References.....	20
6.2. Contact Properties.....	20
6.3. Calendar properties.....	22
6.4. Task properties.....	22
6.5. Note properties.....	23

1. Introduction

This document is intended for developers and administrators who have to manage Sync4j SyncConnector Exchange 1.0.x. It includes:

- Architectural Overview
- Configuration and Administration

1.1. Comments and Feedbacks

The Sync4j Project team wants to hear from you! Please submit your questions, comments, feedbacks or testimonials to sync4j-users@lists.sourceforge.net.

2. Architecture

This section describes the architecture of the SyncConnector Exchange.

2.1. The Big Picture

The system architecture of the SyncConnector Exchange is shown in Figure 1.




Figure 1 - Sync4j SyncConnector Exchange high level architecture

PIM data are stored in the Microsoft Exchange store and are managed by the Microsoft Exchange Server. When SyncServer receives a synchronization request from a client addressed to one of the ExchangeSyncSource, the Local cache is queried for latest updates and, if any item has been updated client side or server side, the ExchangeSyncSource talks to the Exchange server through the WebDAV protocol. The Local cache is updated on regular basis by a scheduled process, the DiffSniffer.

SyncConnector Exchange is administered with a dedicated plug-in for the SyncServer administration tool SyncAdmin by which an administrator can create/modify/delete ExchangeSyncSources.

2.2. SyncServer – Exchange Server Communication

The remote access protocol recommended by Microsoft in a distributed environment is WebDAV.

The WebDAV protocol is an extension to HTTP that you can use to build Web applications that are writable. Using WebDAV protocol methods, you can create, copy, delete, move, or search for resources in the Exchange store as well as set and search for resource properties.

The RFC 2518 specification defines extensions to the Hypertext Transfer Protocol 1.1 (HTTP/1.1), which is defined in RFC 2616. The extensions include a new set of protocol methods and request

headers used to move, copy, delete, and create collections of resources. Additionally, clients can set and get properties about resources along with the resource content itself.

The extensions relating to getting and setting properties require a rich format for data transfer. RFC 2518 defines the XML 1.0 as the format for wire data transfer. Additionally, a namespace in XML is required to provide scope for property names.

For more information about WebDAV see [2] and [3].

2.3. Security

Being WebDAV an HTTP based protocol, security and authentication is based on HTTP security and authentication.

NOTE: a standard Microsoft Exchange installation includes the WebDAV interface, which is based on IIS as web server. By default, IIS is configured to use the proprietary authentication protocol NTLM, which is implemented only in Internet Explorer. Since the ExchangeSyncSource uses raw HTTP requests to the Exchange server, IIS must be configured to use basic authentication. This is done through the Exchange System Manager, changing the options available on the panel *Administrative Groups / First Administrative Group / Servers / [server] / Protocols / Http / Exchange Virtual Server / Exchange*.

Authentication is also the mechanism used by Exchange server to support multiuser. When a WebDAV request is served, it allows to operate only with data belonging to the requesting user.

2.3.1. SyncServer Authentication

Because of the described security model, the SyncServer should skip its own authentication done via properties files or database. This is easily done configuring SyncServer to use `sync4j.framework.security.SimpleOfficier` instead of the default `JAASOfficier`.

In the case of specific needs with different authentication mechanisms can be implemented developing a custom `javax.security.auth.spi.LoginModule`.

2.4. ExchangeSyncSource

The ExchangeSyncSource is the mean the SyncServer interacts with the Exchange store. To do so, the sync source implements the needed WebDAV requests and interprets the received responses.

Because of differences in item handling between different item types (contacts, events, task, notes), four versions of ExchangeSyncSource are provided:

- `sync4j.exchange.engine.source.ExchangeContactSyncSource`
- `sync4j.exchange.engine.source.ExchangeCalendarSyncSource`
- `sync4j.exchange.engine.source.ExchangeTaskSyncSource`
- `sync4j.exchange.engine.source.ExchangeNoteSyncSource`

All those classes, as any sync source, implement the `sync4j.framework.engine.source.SyncSource` interface and extend `sync4j.exchange.engine.source.ExchangeSyncSource`.

2.4.1. WebDAV

The Exchange store is a container of item, where each single item can, in turn, contains other item (in the case of folder items) or properties (in the case of data items).

Properties items can be queried and modified by a remote client through the WebDAV protocol. This is based on an extension of the HTTP protocol as transport protocol and on an XML based RPC protocol by which it is possible to query and modify items and properties.

The Exchange store is based on the item types shown in Figure 2. In this figure, item types are represented as groups of properties identified by an XML namespace.




Figure 2 - Exchange store schema

The full list of the properties for each item type contact, appointment, task, note is available in Appendix A.

3. Installation and Administration

The SyncConnector Exchange is administered and configured through the SyncAdmin interface. In this section, it is presented how to set up the SyncServer database in order to have the connector configured and the panel used to create and configure new sync sources based on the registered sync source types.

3.1. SyncConnector Exchange Registration

The connector is distributed as a SyncServer module (see [6]), therefore the connector registration code is added to the install.xml and *.sql files.

In the case of the SyncConnector Exchange, no additional information is needed in install.xml. Instead, init_schema.sql must contain the SQL code that registers each piece of the connector. The goal is to see the hierarchy of Figure 3.




Figure 3 - SyncConnector Exchange registration

To achieve this, the following data must be inserted:

SYNC4J_MODULE		
moduleid	modulename	description
exc-1.0	syncconnectorexchange-1.0	SyncConnector Exchange 1.0

SP_SS_CONNECTOR			
id	name	description	admin_class
exc-1.0	SyncConnectorExchange	SyncConnector Exchange	

SYNC4J_SYNC_SOURCE_TYPE			
id	description	class	admin_class
exc-ca-1.0	Exchange Calendar SyncSource	sync4j.exchange.engine.source.ExchangeCalendarSyncSource'	sync4j.exchange.admin.ExchangeSyncSourceConfigPanel
exc-co-1.0	Exchange Contacts SyncSource	sync4j.exchange.engine.source.ExchangeContactSyncSource'	sync4j.exchange.admin.ExchangeSyncSourceConfigPanel

SYNC4J_SYNC_SOURCE_TYPE			
exc-ta-1.0	Exchange Tasks SyncSource	sync4j.exchange.engine.source.ExchangeTaskSyncSource'	sync4j.exchange.admin.ExchangeSyncSourceConfigPanel
exc-no-1.0	Exchange Notes SyncSource	sync4j.exchange.engine.source.ExchangeNoteSyncSource'	sync4j.exchange.admin.ExchangeSyncSourceConfigPanel

SP_SS_MODULE_CONNECTOR	
<i>module</i>	<i>connector</i>
exc-1.0	exc-1.0

SP_SS_CONNECTOR_SYNC_SOURCE_TYPE	
<i>connector</i>	<i>sourcetype</i>
exc-1.0	exc-ca-1.0
exc-1.0	exc-co-1.0
exc-1.0	exc-ta-1.0
exc-1.0	exc-no-1.0

3.2. Configuration

The following configuration properties are defined in ExchangeSyncSource:

Property	Description
encode	Should the Data content be encoded?
host	The Exchange server hostname/ip address.
name	The SyncSource name.
port	The Exchange server port.
sourceInfo	The sync source info to use in device capabilities.
sourceURI	The sync source URI.
tmz	Timezone of the machine hosting the Exchange server.
type	The Data content mime type.

Note that encode, host, port and schedule are defined by ExchangeSyncSource, name, sourceInfo and sourceURI are defined by sync4j.framework.engine.source.AbstractSyncSource.

4. Internal design

The following sections describe how SyncConnector Exchange manages internal data and the algorithm for data synchronization. This information is not meant for administrator but for developers looking to extend the capabilities of SyncConnector Exchange.

4.1. Overview

SyncConnector Exchange is composed of the logical modules shown in the collaboration diagram of Figure 4.




Figure 4 - SyncConnector Exchange collaboration diagram

The table below describes the role of each group of classes.

ExchangeContactSyncSource, ExchangeCalendarSyncSource, ExchnageTaskSyncSource, ExchangeNoteSyncSource	<p>This are the components to be plugged into the synchronization engine. They are implementation of the sync4j.framework.engine.source.SyncSource interface. These classes make use of the corresponding manager classes of the above layer in order to access the data layer.</p> <p>Not displayed by the figure, sync source and manager objects deal with the item data by the mean of the model classes Event, Contact, Task, Note.</p>
CalendarManager, ContactManager, TaskManager, NoteManager	This classes create an interface layer on top of the data access layer and include the logic to retrieve the data associated to the items and to combine them in the model classes.
CalendarDAO, ContactDAO, TaskDAO, NoteDAO	<p>This layer abstracts the access to the datasource (database for items status and Exchange store).</p> <p>The WebDAV XML messages returned by the Exchange server are parsed by WebDavXmlParser.</p>
WebDavXmlParser	Is the class that interprets the WebDAV messages obtained by the server.
WebDavHttpTransport	This is the class that implements the connection logic to the Exchange server.

4.2. Items Identification

Any item in the Exchange store is addressed by a resource address and identified by a user-id. The resource address identifies an item by its name and position. For example /contact/home/John Brown.eml addresses a contact stored in a resource called John Brown.eml under the home subfolder.

The resource address is used mainly for update and delete operations, since they require to specify which resource is involved.

However, the resource url cannot be considered a long-term identification key because an item can be moved under different folders. For the purpose of uniquely identify an object in the Exchange store, the property repl-uid is used as it is associated to any item in the store.

The issue of creating new items in the Exchange store is resolved constructing a resource url as follows:

/<user>/<source uri>/<now timestamp>.eml

The item repl-uid assigned by Exchange is returned in the WebDAV response header as in the following example:

```
HTTP/1.1 207 Multi-Status
Server: Microsoft-IIS/5.0
Date: Tue, 20 Jan 2004 15:37:02 GMT
MS-Exchange-Permanent-URL: http://192.168.0.10/Exchange/fabio/-
FlatUrlSpace-/5eb
c95ae2cdf504c98296172915e02d2-5d/5ebc95ae2cdf504c98296172915e02d2-3e26
Repl-UID: <rid:5ebc95ae2cdf504c98296172915e02d2000000003e26>
Content-Type: text/xml
Content-Length: 436
ResourceTag:
<rt:5ebc95ae2cdf504c98296172915e02d2000000003e265ebc95ae2cdf504c982
96172915e02d2000000004dbb>
```

4.3. Detecting and Applying Item Changes

Two important properties stored along with an item in the Exchange store are `<a:creationdate>` and `<a:getlastmodified>` whose return respectively the item creation date and the item last modification timestamp. These properties are important when a fast sync is performed, since the sync source should query for changes happened since the last synchronization. However, when an item is physically deleted from the Exchange store, it disappears from the system and then there is no way to retrieve it or retrieve when it was deleted.

Therefore, a local items cache is needed in order keep track of the existing items at the time of the last synchronization. We call this database the *Local cache*.

The algorithm for changes detection is the following:

1. read all items repl-uid, resourceName, creationDate, lastModified from the Exchange store and put them in `exchangeItems`
2. read all items repl-id, lastModified, from the local cache and put them in `localItems`
3. foreach item `i` in `exchangeItems`
 1. if `i` is in `localItems`
 1. if `i.lastModified != localItems (i) lastModified`
 1. `i` is updated
 2. end if
 2. else
 1. `i` is new
 3. end if
4. foreach item `i` in `localItems`
 1. if `i` is not in `exchangeItems`
 1. `i` is deleted
 2. endif
5. endforeach

This procedure is executed in the `ExchangeSyncSource's beginSync()` method if the sync mode is one of the fast sync modes. The retrieved new, updated and deleted items are temporarily stored until the corresponding `getNew/Updated/DeletedSyncItem()` methods are called. When either `getNewSyncItems()` or `getUpdatedSyncItems()` are called by the sync engine, the corresponding items content is fetched by the Exchange store with proper WebDAV calls. All items must be returned in a single call.

Note that in the comparison steps, uids are compared and not resource urls.

If the sync mode is one of the slow sync modes, no step in the algorithm is done. When `getAllSyncItem()` is called by the sync engine, the items properties are fetched directly from the Exchange store, possibly in one single WebDAV call.

If the client sends items to add to the Exchange store, the new resource is created and the returned uid is added to the local cache.

In the case of client updates or deletes, the uid is used to look up the resource address in the `exchangeItems` list so that the obtained address can be used in the WebDAV call.

In the sync source's `endSync()` method read from Exchange Server the existing items, and are stored in the local cache (after cleaning it).

4.4. Local Cache Database

The local cache database is composed of the following tables:

SS_EXCH_ITEM_STATUS			
id	varchar(200)	primary key	Item unique identifier (repl-uid) in the syncsource specified by uri.
uri	varchar(128)	primary key	SyncSource uri.
principal	varchar(10)	index	Item owner.
last_modified	timestamp		item last modified on Exchange Server

Note that items ids are stored with their owner, who is the principal associated to the user who is performing the sync.

4.5. Error Handling

Any error should happen in the sync source results in a SyncSourceException being thrown. The error condition is logged before throwing the exception and optionally the cause can be set to the originating exception.

4.6. SyncConnector – Exchange dialog examples

The following sections show some examples on how SyncConnector Exchange interacts with Exchange server through WebDAV.

4.6.1. Adding a contact:

```
PROPPATCH /Exchange/fabio/contacts/luigiafassina.eml HTTP/1.1
Host: 192.168.0.10
Content-Type: text/xml
Content-Length: 741
Authorization: Basic ZmFiaW86ZmFiaW8x

<?xml version="1.0" encoding="utf-8" ?>
<D:propertyupdate                                xmlns:D="DAV:"
xmlns:EX="http://schemas.microsoft.com/exchange/"
xmlns:HM="urn:schemas:contacts:">
  <D:set>
    <D:prop>
      <D:contentclass>urn:content-classes:person</D:contentclass>
      <EX:outlookmessageclass>IPM.Contact</EX:outlookmessageclass>
      <HM:cn>Luigia Fassina</HM:cn>
      <HM:nickname>Lu</HM:nickname>
      <HM:email1>luigia.fassina@sync4j.org</HM:email1>
      <HM:title>Luigia Fassina</HM:title>
      <HM:fileas>luigiafassina</HM:fileas>
      <HM:givenName>Luigia</HM:givenName>
    </D:prop>
  </D:set>
</D:propertyupdate>
```

luigiafassina.eml on the first line is the key that uniquely identifies the item.

4.6.2. Updating a Contact

```
PROPPATCH /Exchange/fabio/contacts/luigiafassina.eml HTTP/1.1
Host: 192.168.0.10
Content-Type: text/xml
Content-Length: 741
Authorization: Basic ZmFiaW86ZmFiaW8x

<?xml version="1.0" encoding="utf-8" ?>
```

```

<D:propertyupdate                                     xmlns:D="DAV:"
xmlns:EX="http://schemas.microsoft.com/exchange/"
xmlns:HM="urn:schemas:contacts:">
  <D:set>
    <D:prop>
      <D:contentclass>urn:content-classes:person</D:contentclass>
      <EX:outlookmessageclass>IPM.Contact</EX:outlookmessageclass>
      <HM:cn>Luigia Fassina</HM:cn>
      <HM:nickname>Lu</HM:nickname>
      <HM:email1>lu@sync4j.org</HM:email1>
      <HM:title>Luigia Fassina</HM:title>
      <HM:fileas>luigiafassina</HM:fileas>
      <HM:givenName>Luigia</HM:givenName>
    </D:prop>
  </D:set>
</D:propertyupdate>

```

4.6.3. Listing Contacts

```

PROPFIND /Exchange/fabio/contacts HTTP/1.1
Host: 192.168.0.10
Depth: 1,noroot
Range: rows=0-9
Content-Type: text/xml
Content-Length: 741
Authorization: Basic ZmFiaW86ZmFiaW8x

```

```

<?xml version="1.0" encoding="utf-8" ?>
<D:propfind                                     xmlns:D="DAV:"
xmlns:EX="http://schemas.microsoft.com/exchange/"
xmlns:HM="urn:schemas:contacts:">
  <D:allprop/>
</D:propfind>

```

This example returns all fabio's contacts.

4.6.4. Deleting a Contact

```

DELETE /Exchange/fabio/contacts/luigiafassina.eml HTTP/1.1
Host: 192.168.0.10
Content-Length: 50
Authorization: Basic ZmFiaW86ZmFiaW8x

```

4.6.5. Response to a Successful Addition

```

HTTP/1.1 207 Multi-Status
Server: Microsoft-IIS/5.0
Date: Tue, 20 Jan 2004 15:31:28 GMT
MS-Exchange-Permanent-URL: http://192.168.0.10/Exchange/fabio/-
FlatUrlSpace-/5eb
c95ae2cdf504c98296172915e02d2-5d/5ebc95ae2cdf504c98296172915e02d2-3e26
Repl-UID: <rid:5ebc95ae2cdf504c98296172915e02d2000000003e26>
Content-Type: text/xml
Content-Length: 477
ResourceTag:
<rt:5ebc95ae2cdf504c98296172915e02d2000000003e265ebc95ae2cdf504c982
96172915e02d2000000004db6>
MS-WebStorage: 6.0.6249

```

```
<?xml
                                version="1.0"?><a:multistatus
xmlns:b="http://schemas.microsoft.com/exchange/"
xmlns:c="urn:schemas:contacts:" xmlns:a="DAV:">
<a:response>
<a:href>http://192.168.0.10/Exchange/fabio/Contacts/Johnniepippol.eml</a:hr
ef>
<a:status>HTTP/1.1    201    Created</a:status><a:propstat><a:status>HTTP/1.1
200 OK</a:status>
<a:prop>
  <a:contentclass/><b:outlookmessageclass/><c:cn/><c:nickname/><c:email1/><c
:title/><c:fileas/><c:givenName/></a:prop></a:propstat></a:response></a:mu
ltistatus>
```

The operation status is specified by the line:

```
<a:status>HTTP/1.1 201 Created</a:status>
```

4.6.6. Response to a Successful Update

```
HTTP/1.1 207 Multi-Status
Server: Microsoft-IIS/5.0
Date: Tue, 20 Jan 2004 15:37:02 GMT
MS-Exchange-Permanent-URL:      http://192.168.0.10/Exchange/fabio/-
FlatUrlSpace-/5eb
c95ae2cdf504c98296172915e02d2-5d/5ebc95ae2cdf504c98296172915e02d2-3e26
Repl-UID: <rid:5ebc95ae2cdf504c98296172915e02d2000000003e26>
Content-Type: text/xml
Content-Length: 436
ResourceTag:
<rt:5ebc95ae2cdf504c98296172915e02d2000000003e265ebc95ae2cdf504c982
96172915e02d2000000004dbb>
MS-WebStorage: 6.0.6249
```

```
<?xml
                                version="1.0"?><a:multistatus
xmlns:b="http://schemas.microsoft.com/exchan
ge/"
                                xmlns:c="urn:schemas:contacts:"
xmlns:a="DAV:"><a:response><a:href>http://192.168.0.10/Exchange/fabio/Contacts/Johnniepippol.eml</a:href><a:propstat>
<a:sta
tus>HTTP/1.1
                                200
OK</a:status><a:prop><a:contentclass/><b:outlookmessageclass/><
c:cn/><c:nickname/><c:email1/><c:title/><c:fileas/><c:givenName/></a:prop>
</a:pr
opstat></a:response></a:multistatus>
```

4.6.7. Response to a Failed Addition (not Existing URN)

```
HTTP/1.1 409 Conflict
Server: Microsoft-IIS/5.0
Date: Tue, 20 Jan 2004 15:41:51 GMT
Connection: close
Content-Type: text/html
Content-Length: 140
MS-WebStorage: 6.0.6249
```

```
<body><h2>HTTP/1.1 409 Conflict</h2></body></HTML>; charset=utf-8">
```

4.6.8. Response to a Successfully Deletion

```
HTTP/1.1 200 OK
Server: Microsoft-IIS/5.0
Date: Tue, 20 Jan 2004 15:45:43 GMT
Content-Length: 0
ResourceTag: <rtd:5ebc95ae2cdf504c98296172915e02d2000000003e26>
MS-WebStorage: 6.0.6249
```

4.6.9. Response to a Failed Deletion (Unexisting Contact)

```
HTTP/1.1 404 Resource Not Found
```

```
Server: Microsoft-IIS/5.0
Date: Tue, 20 Jan 2004 15:43:54 GMT
Connection: close
Content-Type: text/html
Content-Length: 4040
MS-WebStorage: 6.0.6249
```

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 3.2 Final//EN">
<html dir=ltr>
```

```
<head>
<style>
a:link           {font:8pt/11pt verdana; color:FF0000}
a:visited        {font:8pt/11pt verdana; color:#4e4e4e}
</style>
```

```
<META NAME="ROBOTS" CONTENT="NOINDEX">
```

```
<title>The page cannot be found</title>
```

```
L'errore indicato è:
HTTP/1.1 404 Resource Not Found
```

4.6.10. Adding an Appointment

```
PROPPATCH /Exchange/fabio/calendar/calendarprova.eml HTTP/1.1
Host: 192.168.0.10
Content-Type: text/xml
Content-Length: 741
Authorization: Basic ZmFiaW86ZmFiaW8x
```

```
<?xml version="1.0" encoding="utf-8" ?>
<D:propertyupdate                                     xmlns:D="DAV:"
xmlns:EX="http://schemas.microsoft.com/exchange/"
xmlns:HM="urn:schemas:calendar:" xmlns:e="urn:schemas:httpmail:">
  <D:set>
    <D:prop>
      <D:contentclass>urn:content-classes:appointment</D:contentclass>
      <EX:outlookmessageclass>IPM.Appointment</EX:outlookmessageclass>
      <e:subject>oggi telefonare al signor verri</e:subject>
      <HM:location>meetappt Location</HM:location>
      <HM:dtstart>2004-01-10T22:00:00.000Z</HM:dtstart>
      <HM:dtend>2004-01-10T22:30:00.000Z</HM:dtend>
    </D:prop>
  </D:set>
</D:propertyupdate>
```

4.6.11. Updating an Appointment

```
PROPPATCH /Exchange/fabio/calendar/calendarprova.eml HTTP/1.1
Host: 192.168.0.10
Content-Type: text/xml
Content-Length: 741
Authorization: Basic ZmFiaW86ZmFiaW8x
```

```
<?xml version="1.0" encoding="utf-8" ?>
<D:propertyupdate                                xmlns:D="DAV:"
xmlns:EX="http://schemas.microsoft.com/exchange/"
xmlns:HM="urn:schemas:calendar:" xmlns:e="urn:schemas:httpmail:">
  <D:set>
    <D:prop>
      <D:contentclass>urn:content-classes:appointment</D:contentclass>
      <EX:outlookmessageclass>IPM.Appointment</EX:outlookmessageclass>
      <e:subject>oggi telefonare al signor rossi</e:subject>
      <HM:location>meetappt Location</HM:location>
      <HM:dtstart>2004-01-10T22:00:00.000Z</HM:dtstart>
      <HM:dtend>2004-01-10T22:30:00.000Z</HM:dtend>
    </D:prop>
  </D:set>
</D:propertyupdate>
```

4.6.12. Listing Appointments

```
PROPFIND /Exchange/fabio/calendar HTTP/1.1
Host: 192.168.0.10
Depth: 1,noroot
Range: rows=0-9
Content-Type: text/xml
Content-Length: 741
Authorization: Basic ZmFiaW86ZmFiaW8x
```

```
<?xml version="1.0" encoding="utf-8" ?>
<D:propfind                                xmlns:D="DAV:"
xmlns:EX="http://schemas.microsoft.com/exchange/"
xmlns:HM="urn:schemas:calendars:">
  <D:allprop/>
</D:propfind>
```

4.6.13. Deleting an Appointment

```
DELETE /Exchange/fabio/calendar/calendarprova.eml HTTP/1.1
Host: 192.168.0.10
Content-Length: 50
Authorization: Basic ZmFiaW86ZmFiaW8x
```

4.6.14. Selecting Appointment Items Modified after a Given Date

WebDAV defines an SQL-like language through which execute generic queries on the Exchange store.

```
SEARCH /Exchange/fabio/calendar HTTP/1.1
Host: 192.168.0.10
Depth: 1,noroot
Range: rows=0-7
Content-Type: text/xml
Content-Length: 741
```


Authorization: Basic ZmFiaW86ZmFiaW8x

```
<?xml version="1.0" encoding="utf-8" ?>
<D:searchrequest xmlns:D = "DAV:" >
  <D:sql>
    Select  "urn:schemas:calendar:location" AS location,
            "urn:schemas:httpmail:subject" AS subject FROM
"/Exchange/fabio/calendar" WHERE "D:getlastmodified" > '1999/09/27
00:00:00'
  </D:sql>
</D:searchrequest>
```

5. Sync4j Licensing

The Sync4j software is released under the “GNU General Public License” (“GPL”). This means that Sync4j can be used free of charge under the “GPL”. If you do not want to be bound by the “GPL” terms (such as the requirement that your application must also be “GPL”, you may purchase a commercial license for the same product from Funambol; contact Funambol at sales@funambol.com .

Since Funambol owns the copyright to the Sync4j source code, we are able to employ “Dual Licensing”, which means that the same product is available under “GPL” and under a commercial license. This does not in any way affect the “Open Source” commitment of Funambol. For details about when a commercial license is required, please see the Copyrights and Licensing section of this manual.

5.1. Copyrights and Licenses Used by Funambol

Funambol owns the copyright to the “Sync4j” source code.

All the source code in the Sync4j software is covered by the “GNU General Public License”. The text of this license can be found as the file 'COPYING' in the distribution.

The “*GNU General Public License*” (“GPL”) is probably the best known *Open Source* license. The formal terms of the “GPL” license can be found at <http://www.fsf.org/licenses/>. See also <http://www.fsf.org/licenses/gpl-faq.html> and <http://www.gnu.org/philosophy/enforcing-gpl.html>.

Since the “Sync4j” software is released under the “GPL”, it may often be used for free, but for certain uses you may want or need to buy commercial licenses from “Funambol”. Contact Funambol at sales@funambol.com for more information.

5.2. Using the Sync4j Software Under a Commercial License

The “GPL” license is contagious in the sense that when a program is linked to a “GPL” program all the source code for all the parts of the resulting product must also be released under the “GPL”. If you do not follow this “GPL” requirement, you break the license terms and forfeit your right to use the “GPL” program altogether. You also risk damages.

You need a commercial license:

- When you link a program with any “GPL” code from the “Sync4j” software and don't want the resulting product to be licensed under “GPL”, perhaps because you want to build a commercial product or keep the added non-“GPL” code closed source for other reasons. When purchasing commercial licenses, you are not using the “Sync4j” software under “GPL” even though it's the same code.

- When you distribute a non-"GPL" application that *only* works with the "Sync4j" software and ship it with the "Sync4j" software. This type of solution is considered to be linking even if it's done over a network.
- When you distribute copies of the "Sync4j" software without providing the source code as required under the "GPL" license.
- When you want to support the further development of the "Sync4j" even if you don't formally need a commercial license.
Purchasing support directly from "Funambol" is another good way of contributing to the development of the "Sync4j" software, with immediate advantages for you.

For commercial licenses, please contact Funambol at sales@funambol.com.

5.3. Using the Sync4j Software for Free Under GPL

You can use the "Sync4j" software for free under the "GPL" if you adhere to the conditions of the "GPL". Common uses of the "GPL" include:

- When you distribute both your own application and the "Sync4j" source code under the "GPL" with your product.
- When you distribute the "Sync4j" source code bundled with other programs that are not linked to or dependent on the "Sync4j" system for their functionality even if you sell the distribution commercially.
This is called mere aggregation in the "GPL" license.
- When you are not distributing *any* part of the "Sync4j" system, you can use it for free.

If your use of "Sync4j" software does not require a commercial license, we encourage you to purchase support from "Funambol" anyway.

This way you contribute toward "Sync4j" development and also gain immediate advantages for yourself.

If you use the "Sync4j" software in a commercial context such that you profit by its use, we ask that you further the development of the "Sync4j" software by purchasing some level of support. We feel that if the "Sync4j" helps your business, it is reasonable to ask that you help "Funambol". (Otherwise, if you ask us support questions, you are not only using for free something into which we've put a lot a work, you're asking us to provide free support, too.)

6. Appendices

6.1. References

- [1] *SyncConnector Exchange Requirements Document*, October 2003
- [2] <http://www.webdav.org>
- [3] http://msdn.microsoft.com/library/default.asp?url=/library/en-us/wss/wss/wss_references_webdav.asp
- [4] Quartz Enterprise Job Scheduler, <http://www.quartzscheduler.org>
- [5] JBoss Administration and Development, Second Edition
- [6] Sync4j Modules Development Guide, Sync4j, February 2004

6.2. Contact Properties

The following properties are associated to an Exchange contact item and supported by the connector:

General	
First name	<sn>
Last name	<givenName>
Middle name	<middleName>
Title	<title>
Organization	<o>
Nick name	<nickname>
Spouse name	<spousecn>
Initials	<initials>
Common name	<cn>
File as	<fileas>
Home address	
Home street	<homeStreet>,<mailingstreet>
Home city	<homeCity>,<mailingcity>
Home state	<homeState>,<mailingstate>
Home postal code	<homePostalCode>,<mailingpostalcode>
Home country	<homeCountry>,<mailingcountry>
Home address	<homepostaladdress>,<mailingpostaladdress>
Business address	
Street	<street>

City	< >
State/Prov	<st>
Postal code	<postalcode>
Country	<co>
Business address	<workpostaladdress>
Other address	
Street	<otherStreet>
City	<othercity>
State/Prov	<otherstate>
Postal code	<otherpostacode>
Country	<othercountry>
Other address	<otherpostaladdress>
Contact info	
Home phone number	<homePhone>
Home phone number 2	<homephone2>
Business phone number1	<telephoneNumber>
Business phone number2	<telephonenumber2>
Mobile phone number	<mobile>
Secretary phone number	<secretaryphone>
Home fax number	<homefax>
Business fax number	<facsimiletelephonenumber>
Callback phone number	<callbackphone>
Other mobile phone number	<othermobile>
Organization main phone number	<organizationmainphone>
International ISDN number	<internationalisdnnnumber>
Other phone number	<otherTelephone>
Other fax	<otherfax>
Pager	<pager>
Emails (1,2,3)	<email1>,<email2>,<email3> ¹
Business info	
Department	<department>
Room number	<roomnumber>
Profession	<profession>
Manager	<manager>
Secretary name	<secretarycn>
Additional info	
Business home page	<businesshomepage>

¹ In the form “<display name>” <emailaddress> (e.g.: “John Brown” <john.brown@somewhere.com>)

Other internet address	<fburl>
Text description	<textdescription>
HTML description	<htmldescription>
Timestamping	
Creation date	<creationdate>
Last modified	<getlastmodified>
Identification	
UID	<repl-uid>

6.3. Calendar properties

General	
subject	<subject>
location	<location>
dtstart	<dtstart>
dtend	<dtend>
duration	<duration>
alldayevent	<alldayevent>
sequence	<sequence>
timezone	<timezone>
bustatus	<bustatus>
meetingstatus	<meetingstatus>
Timestamping	
Creation date	<creationdate>
Last modified	<getlastmodified>
Identification	
UID	<repl-uid>

6.4. Task properties

General	
subject	<subject>
date	<date>
Timestamping	
Creation date	<creationdate>
Last modified	<getlastmodified>
Identification	
UID	<repl-uid>

6.5. Note properties

General	
subject	<subject>
date	<date>
description	<description>
Timestamping	
Creation date	<creationdate>
Last modified	<getlastmodified>
Identification	
UID	<repl-uid>