

[DocV1.Overidethedefaultdatabaseserviceconfiguration](#)

Override the default database service configuration

The next XML configuration fragment allows you to bind the datasource used by the eXo platform services to a real datasource JNDI name as defined in your application server. You can add as many datasource you wish and then use them through the DatanaseService or the HibernateService.

```
<service-configuration
key="org.exoplatform.services.database.DatabaseService"
type="org.exoplatform.services.database.impl.DatabaseServiceImpl">
<object-param> <name>database.service.config</name>
<type>org.exoplatform.services.database.impl.DatabaseServiceConfig</type>
<property name="datasource[0]" value="#new
DatabaseServiceConfig$DataSourceConfig" /> <property
name="datasource[0].name" value="ExoDS" /> <property
name="datasource[0].jndi" value="jdbc/ic3DS" /> <property
name="datasource[1]" value="#new DatabaseServiceConfig$DataSourceConfig"
/> <property name="datasource[1].name" value="WorkflowDS" /> <property
name="datasource[1].jndi" value="jdbc/ic3WorkflowDS" /> <!-- <property
name="datasource[2]" value="#new DatabaseServiceConfig$DataSourceConfig"
/> <property name="datasource[2].name" value="ThirdPartyDS" /> <property
name="datasource[2].jndi" value="jdbc/ThirdPartyDS" /> -->
</object-param> </service-configuration>
```

[DocV1.Overidethedefaultdatabaseserviceconfiguration](#) (en)

Cr ateur: XWiki.benjamin.mestrallet Creation Date: 2005/02/11 00:36

Dernier Auteur: XWiki.benjamin.mestrallet Last Modification Date: 2005/02/11 00:39

Copyright 2004 (c) Auteurs des pages